Customer No.: 31561 Docket No.: 13321-US-PA

Application No.: 10/711,472

## **AMENDMENT**

Please amend the application as indicated hereafter.

## In the Claims:

Claim 1 (previously presented) A method of IP characterization, comprising:

providing an IP component;

automatically generating a plurality of test patterns for all paths in the IP component;

sequentially inputting the test patterns into the IP component for simulation, and

outputting a plurality of corresponding simulation results; and

extracting at least one key data from each of the simulation results, respectively; and

integrating the key data of each of the simulation results to generate the IP

characteristic library.

Claim 2 (original) The method of IP characterization of claim 1, wherein the step of

automatically generating the plurality of test patterns for all paths in the IP component

comprises:

automatically searching all of the paths in the IP component; and

generating the corresponding test patterns for each of the paths.

Claim 3 (original) The method of IP characterization of claim 2, wherein the step of

automatically searching all of the paths in the IP component comprises:

identifying and excluding an ESD path;

Customer No.: 31561

Docket No.: 13321-US-PA Application No.: 10/711,472

wherein if there is at least a path point which has not been completely searched, the

path point is selected;

determining whether one of the paths of the selected path point reaches an end point

of the path or not;

searching a next path point connected by one of the paths of the selected path point

by selecting a connection terminal of a transistor based on a transistor rule; and

searching a next path point connected by one of the paths of the selected path point

by selecting a connection terminal of a resistor based on a resistor rule.

Claim 4 (original) The method of IP characterization of claim 3, wherein the step of

automatically searching all of the paths in the IP component further comprises:

analyzing a type of all of the I/O ports in the IP component; and

comparing the I/O ports of the IP component with an I/O port information stored in a

database.

Claim 5 (original) The method of IP characterization of claim 4, wherein the type of

the I/O ports comprises an input port, an output port and a bi-directional port.

Claim 6 (original) The method for IP characterization of claim 3, wherein the step of

automatically searching all of the paths in the IP component further comprises excluding

any path which is input/output from any of the I/O ports in the IP component not passing

through any circuitry in the IP component.

3 .

Customer No.: 31561 Docket No.: 13321-US-PA

Application No.: 10/711,472

Claim 7 (cancelled)

Claim 8 (original) The method of IP characterization of claim 1, wherein the IP

characteristic library comprises a plurality of timing information and a plurality of power

information corresponding to the test patterns.

Claim 9 (original) The method for IP characterization of claim 1, wherein the IP

component is configured by a Hardware Description Language (HDL).

Claim 10 (previously presented) A method of finding paths in an IP component,

comprising: providing an IP component;

identifying and excluding an ESD path; wherein if there is at least a path point which

has not been completely searched yet, the path point is selected;

determining whether or not one of the paths of the selected path point reaches an end

point of the path;

searching a next path point connected by one of the paths of the selected path point

by selecting a connection terminal of a transistor based on a transistor rule; and

searching a next path point connected by one of the paths of the selected path point

by selecting a connection terminal of a resistor based on a resistor rule.

Claim 11 (previously presented) The method of finding paths in an IP component of

claim 10, further comprising: analyzing a type of all of the I/O ports in the IP component;

Customer No.: 31561

Docket No.: 13321-US-PA

Application No.: 10/711,472

and comparing the I/O ports of the IP component with an I/O port information stored in a

database.

Claim 12 (previously presented) The method of finding paths in an IP component of

claim 11, wherein a type of the I/O ports comprises an input port, an output port and a

bi-directional port.

Claim 13 (previously presented) The method of finding paths in an IP component of

claim 10, further comprising excluding any path which is input/output from any of the I/O

ports in the IP component not passing through any circuitry in the IP component.

Claim 14 (previously presented) The method of finding paths in an IP component of

claim 10, wherein the IP component is configured by a Hardware Description Language

(HDL).

Claim 15 (currently amended) A computer readable recording storage medium for

storing having [[a]] computer readable executable program instructions for executing

performing an IP characterization method on a computer system, the IP characterization

method comprises::

reading an IP component;

automatically generating a plurality of test patterns for all paths in the IP component;

sequentially reading each of the test patterns for performing simulation on the IP

Customer No.: 31561 Docket No.: 13321-US-PA

Application No.: 10/711,472

component and generating a plurality of corresponding simulation results; and

extracting at least one key data from each of the simulation results, respectively; and

integrating the key data of each of the simulation results to generate the IP

characteristic library.

Claim 16 (currently amended) The computer readable recording storage medium of

claim 15, wherein automatically generating the plurality of test patterns for all paths in the

IP component comprises:

automatically searching all of the paths in the IP component; and

generating the corresponding test patterns for each of the paths.

Claim 17 (currently amended) The computer readable recording storage medium of

claim 16, wherein automatically searching all of the paths in the IP component comprises:

identifying and excluding an ESD path;

wherein if there is at least a path point which has not been completely searched, the

path point is selected;

determining whether or not one of the paths of the selected path point reaches an end

point of the path;

searching a next path point connected by one of the paths of the selected path point

by selecting a connection terminal of a transistor based on a transistor rule; and

searching a next path point connected by one of the paths of the selected path point

by selecting a connection terminal of a resistor based on a resistor rule.

Customer No.: 31561

Docket No.: 13321-US-PA

Application No.: 10/711,472

Claim 18 (currently amended) The computer readable recording storage medium of

claim 17, wherein automatically searching all of the paths in the IP component further

comprises:

analyzing a type of all of the I/O ports in the IP component; and

comparing the I/O ports of the IP component with an I/O port information stored in a

database.

Claim 19 (currently amended) The computer readable recording storage medium of

claim 18, wherein a type of the I/O ports comprises an input port, an output port and a

bi-directional port.

Claim 20 (currently amended) The computer readable recording storage medium of

claim 17, wherein automatically searching all of the paths in the IP component further

comprises excluding any path which is input/output from any of the I/O ports in the IP

component and not passed through any circuitry in the IP component.

Claim 21 (cancelled)

Claim 22 (currently amended) The computer readable recording storage medium of

claim 15, wherein the IP characteristic library comprises a plurality of timing information

and a plurality of power information corresponding to the test patterns.

Customer No.: 31561 Docket No.: 13321-US-PA Application No.: 10/711,472

Claim 23 (currently amended) The computer readable recording storage medium of claim 15, wherein the IP component is configured by a Hardware Description Language (HDL).